



## TYPICAL SPECIFICATION

<b>Model Compliance</b>	<b>Harwel HW3 AS1735 Part 3, unrestricted</b>
Drive System Control System Rated Load Capacity Rated Speed Maximum Travel Height No. of Car Entrances Maximum Levels Served Landing Doors & Frames Landing Door Size Passenger Door Protection Machine Room Location Levelling Accuracy Car Operating Panel Car Door Telephone Car Internal Depth Car Internal Width Car Wall Height Ventilation	2:1 roped hydraulic, cantilevered side ram OR direct acting Automatic 544 kg ( 8 passenger) maximum .3 mps maximum 9000 mm 1 or 2 4 floors 2 PSO 900mm COW x 2000mm COH 2000mm 900mm wide x 2000mm high Full height light ray system to car entrance Adjacent to lift shaft Full Load to No Load +/- 5mm 1 C.O.P. to side wall (2 if complying with DDA) with tactile buttons Horizontal sliding, 2 piece side opening Emergency telephone, hands free at C.O.P. 1400mm standard - or as required 1100mm standard - or as required 2100mm high Vents at top & bottom of car
<b>Car Interior Finishes:</b> Side & Rear Walls Car Door Jambs Ceiling Lighting Flooring Handrail Mirror	Choice of laminate/timber veneer or satin stainless Satin stainless White Laminate Two low voltage down lights Black safety rubber or by others 50mm dia. polished stainless steel Half mirror to rear wall
<b>Building Details:</b> Shaft Internal Plan Dimensions Top Overrun Pit Depth Power required Communication	1650mm wide x 1695 mm deep 3300mm clear 1100 mm deep 415v 3 phase 20amp Dedicated link to motor room

**Harwel Lifts Pty Ltd**  
 ABN 87 090 966 402

PO Box 303  
 Gloucester NSW 2422

Ph: 02 6558 9977  
 Fax: 02 6558 9933

email: [harwel@bigpond.com](mailto:harwel@bigpond.com)